Rochester Institute of Technology

RIT Scholar Works

Theses

5-1-1997

Degree of quantization and spatial addressability tradeoffs in perceived quality of color images

Alexander Vaysman

Follow this and additional works at: <https://scholarworks.rit.edu/theses>

Recommended Citation

Vaysman, Alexander, "Degree of quantization and spatial addressability tradeoffs in perceived quality of color images" (1997). Thesis. Rochester Institute of Technology. Accessed from

This Thesis is brought to you for free and open access by RIT Scholar Works. It has been accepted for inclusion in Theses by an authorized administrator of RIT Scholar Works. For more information, please contact ritscholarworks@rit.edu.

Degree of Quantization and Spatial Addressability Tradeoffs in Perceived Quality of Color Images.

by
Alexander Vaysman
B.S. Rochester Institute of Technology
(1994)

A thesis submitted in partial fulfillment of the
requirements for the degree of Master of Science
in the Chester F. Carlson Center of Imaging Science
of the College of Science
Rochester Institute of Technology.

May 1997

Signature of the Author Alexander Vaysman

Accepted by _____
Coordinator, M.S. Degree Program Date _____

CHESTER F. CARLSON
CENTER FOR IMAGING SCIENCE
COLLEGE OF SCIENCE
ROCHESTER INSTITUTE OF TECHNOLOGY
ROCHESTER, NEW YORK

CERTIFICATE OF APPROVAL

M.S. DEGREE THESIS

The M.S. Degree Thesis of Alexander Vaysman
has been examined and approved by the
thesis committee as satisfactory for the
thesis requirement for the
Master of Science degree

Dr. Mark D. Fairchild, Thesis Advisor

Dr. Jonathan S. Arney

Dr. Roger L. Easton

mm 10 1997
Date

THESIS RELEASE PERMISSION
ROCHESTER INSTITUTE OF TECHNOLOGY
COLLEGE OF SCIENCE
CHESTER F. CARLSON
CENTER FOR IMAGING SCIENCE

Title of Thesis "Degree of Quantization and Spatial Addressability
Tradeoffs in Perceived Quality of Color Images"

I, Alexander Vaysman, hereby grant permission to the Wallace
Memorial Library of R.I.T. to reproduce my thesis in whole or in part.
Any reproduction will not be for commercial use or profit.

Signature: _____

Date: May 14, 1997

Degree of Quantization and Spatial Addressability Tradeoffs in Perceived Quality of Color Images.

by
Alexander Vaysman

Submitted to the
Center for Imaging Science
in partial fulfillment of the requirements
for the Master of Science Degree
at the Rochester Institute of Technology

Abstract.

The objective of this thesis research was to investigate the tradeoffs between the number of quantization levels and spatial addressability of printed color images. Image quantization was done by employing the error-diffusion algorithm. The diffusion of error was performed in CMYK color space. The resulting images were printed on a color output device simulating different spatial addressabilities. To evaluate the perceived image quality, a psychophysical experiment was conducted followed by a statistical analysis of the experimental data. Based on the results of this analysis, the conclusions on the tradeoffs between the number of quantization levels and spatial addressability were drawn. It was determined that the tradeoffs were scene dependent with photographic scenes being able to sustain greater reduction in addressability without perceived image quality being decreased than graphics. The experiment showed that photographic scenes were sufficient to be printed with 5 bits per pixel per color at 100 dots per inch, and graphics with 3 bits per pixel per color at 300 dots per inch. If a single bits per color / dots per inch combination is to be named as the optimum combination equivalent to the best possible image for the given system (8bpc/300dpi), it would have to be 3bpc/300dpi. This combination was found to be equivalent to the quality of the best possible image at the normal viewing distance for all scenes in the experiment.

ACKNOWLEDGEMENTS

First of all, I am very grateful to my parents, Bella and Gregory, and my girlfriend, Julia, for their unlimited patience and unconditional support during all the years it took me to obtain my degree.

Many people contributed their time and expertise in assisting me with this thesis research. Dr. Mark Fairchild, my advisor, provided his guidance. Dr. Karen Braun helped with the setup and carry out of the psychophysical experiment. Dr. Reiner Eschbach provided insightful comments and invaluable advice. I would like to thank my coworkers at Xerox Corp., Dr. R. Balasubramanian, Dr. R. de Queiroz, Dr. M. Maltz, Dr. P. Roetling and Ms. J. Stinehour, for their prompt responses to my questions and requests. I would also like to acknowledge my former coworkers at RIT Research Corp., Mr. B. Saunders, Mr. P. Plaisted, Mr. J. A. S. Viggiano and Mr. J. Wang, where I started this thesis research. I thank my thesis committee members, Dr. J. Arney and Dr. R. Easton, for their input and participation. Last but not least, I would like to thank all the persons who participated as observers in the experiment.

Table of Contents

1. Introduction	1
2. Background	4
3. Approach	9
3.1 Image Selection	9
3.2 Image Processing Path	9
3.3 Device Calibration	13
3.4 Test Images	14
3.5 Experiment Setup and Execution	15
3.6 Observer Selection	19
4. Results and Discussion.	21
4.1 Experienced and Inexperienced Observer Differences	21
4.2 "Girl" Scene	22
4.3 "Harbor" Scene	26
4.4 "Train" Scene	26

4.5 Photographic Scenes	33
4.6 Discussion	37
5. Conclusions.	47
6. References.	48
Appendix A: An Example of an Image at Different Spatial and Color Resolutions.	53
Appendix B: Experiment Scenes.	55
Appendix C: Paired t-Test Results of Mean Scale Values with 95% Confidence for Experienced and Inexperienced Observers	58
Appendix D: "Girl" Scene Scale Values.	61
Appendix E: "Harbor" Scene Scale Values.	62

Appendix F: "Train" Scene Scale Values.	63
--	----

Appendix G: Paired t-Test Results of Mean Scale Values with 95%	
---	--

Confidence for "Girl" and "Harbor" Scenes.	64
---	----

List of Figures

Figure 1.1: A 2×2 halftone superpixel.	1
Figure 2.1: The error diffusion algorithm.	5
Figure 2.2: Error diffusion kernels	6
Figure 3.1: The pictorial image processing path.	10
Figure 3.2: The graphic image processing path.	11
Figure 3.3: Error diffusion weights used.	11
Figure 3.4: An example of resolution adjustment steps.	12
Figure 3.5: Experiment instructions.	17
Figure 3.6: Data collection tool GUI.	17

Figure 3.7: The overhead view of the experimental setup.	18
Figure 3.8: Landolt-C acuity test target.	19
Figure 4.1: Scaled image quality for “Girl” scene with number of bits per color as a parameter.	24
Figure 4.2: Scaled image quality for “Girl” scene with addressability as a parameter.	25
Figure 4.3: Scaled image quality for “Harbor” scene with number of bits per color as a parameter.	28
Figure 4.4: Scaled image quality for “Harbor” scene with addressability as a parameter.	29
Figure 4.5: Scaled image quality for “Train” scene with number of bits per color as a parameter.	31

Figure 4.6: Scaled image quality for “Train” scene with addressability as a parameter.	32
Figure 4.7: Scaled image quality for photographic scenes with number of bits per color as a parameter.	35
Figure 4.8: Scaled image quality for photographic scenes with addressability as a parameter.	36
Figure 4.9: “Girl” scene scaled image quality 3-D bar graph.	39
Figure 4.10: “Harbor” scene scaled image quality 3-D bar graph.	40
Figure 4.11: “Train” scene scaled image quality 3-D bar graph.	41
Figure 4.12: Photographic scenes scaled image quality 3-D bar graph. ...	42

List of Tables

Table 3.1: Number of gray levels reproducible on Tektronix Phaser 440. . . .	14
Table 3.2: Physical parameters of presented images.	15
Table 3.3: The observer statistics.	20
Table 4.1: "Girl" scene statistics on image-per-image basis.	23
Table 4.2: "Harbor" scene statistics on image-per-image basis.	27
Table 4.3: "Train" scene statistics on image-per-image basis.	30
Table 4.4: Photographic scenes statistics on image-per-image basis. . . .	34
Table 4.5: Images equivalent to 8bpc/300dpi.	37
Table 4.6: Information capacity for images in the experiment.	44

Table 4.7: “Girl” scene images equivalent to 8bpc/300dpi with ICs.	45
Table 4.8: “Harbor” scene images equivalent to 8bpc/300dpi with ICs.	45
Table 4.9: “Train” scene images equivalent to 8bpc/300dpi with ICs.	45
Table 4.10: Photographic scenes images equivalent to 8bpc/300dpi with ICs.	45

1. Introduction

Since the early days of printing, the challenge of rendering continuous-tone images existed. One of the solutions for the printing industry was bilevel *halftoning*, which is a process based on the integration property of the human eye^{11,16}. It sacrifices spatial resolution in order to create an illusion of multiple intensity levels in an image. Figure 1.1 shows a 2×2 pixel area of a bilevel device which is referred to as a superpixel. As seen, a 2×2 superpixel is capable of reproducing five distinct gray levels: 0, 25, 50, 75, and 100%, at the cost of reducing the spatial resolution by a factor of two along each axis.

Figure 1.1: A 2×2 halftone superpixel.

In general, a $n \times n$ area of bilevel pixels can produce n^2+1 gray levels. However, this is accompanied by the reduction of spatial resolution n times along each axis.

There exists a considerable number of various halftone techniques that

provide acceptable renditions of original continuous tone images²⁷. One of these techniques is *error diffusion*, which was introduced by Floyd and Steinberg in the mid-1970's¹⁰, and is able to produce high-quality reproductions by improving the renditions of detail in an image and appearing less noisy than other halftone techniques. Error diffusion is a sequential algorithm whose feedback mechanism propagates the error due to thresholding to the neighboring pixels that have not yet been quantized.

The original error-diffusion algorithm was intended to produce a bilevel output for monochrome input images. It is not very difficult to adapt this algorithm to produce multilevel output by employing more than one threshold¹⁷. This modification coupled with the capability to print multiple levels made it possible to obtain soft- and hardcopy reproductions of original continuous-tone images with a quality superior to that of bilevel renditions. In addition, the application of error diffusion can easily be extended from monochrome images to color images. For instance, each channel of an RGB or CMYK image may be treated as a single independent monochrome image and error diffused.

Another important issue in printing is the *spatial addressability* or *resolution* of output devices. Spatial addressability refers to how closely adjacent dots may be printed. In general, printing on a device of higher

addressability results in an output of higher quality than that of the output obtained on a lower addressability device.

Multilevel halftoning can be used to compensate for image quality limitations of devices with poor spatial addressability. The relationship of this tradeoff had to be thoroughly investigated. In order to achieve this goal, a psychophysical experiment was conducted to evaluate perceived quality of images quantized to different numbers of levels at different spatial resolutions. Subsequent statistical analysis provided the necessary data to evaluate tradeoffs between the number of quantization levels or color resolution expressed in bits per color (*bpc*), and spatial addressability expressed in dots per inch (*dpi*).

2. Background

In the mid-1960's, digital halftoning algorithms utilizing newly available computing equipment were starting to become available. Since that time, significant advances in digital halftoning have been made. A large number of techniques have been developed^{27,30} which can be categorized by different criteria³⁰ such as type of pattern (periodic or aperiodic), type of "dot" (dispersed or clustered), type of processing operation (point or neighborhood), etc.

Several authors compared the performance of the various techniques^{9,17,22}. Their findings indicate that error diffusion provides the higher-quality renditions of the continuous-tone originals than Bayer's (dispersed-dot) or clustered-dot dithering. The basic concept of binary error diffusion is depicted in Figure 2.1³⁰. The threshold is fixed to 0.5, and the input $J[n]$ takes on values between 0 (white) or 1 (black). The thresholding operation produces the binary output $I[n]$, and the error for the particular location n is the difference between the output and the input: $J[n] - I[n]$. This error is passed through the error filter or kernel $e[n]$ yielding the correction terms to be added to the future input values. This error is "diffused" over a weighted neighborhood as specified by $e[n]$.

Figure 2.1: The error diffusion algorithm.

Since the original error diffusion algorithm was introduced by Floyd and Steinberg in 1975¹⁰, many modifications have been introduced. Each altered some of the parameters of the process such as the kernel size and weights, the threshold values, the order of processing, etc.^{7,20,27,30} For instance, Figure 2.2 shows different error-diffusion kernels. The specified fraction of the thresholding error is distributed over the indicated unprocessed pixels. Some authors examined the effects of the response of the human visual system on the perception error diffusion^{21,22,29}. These modifications result in various degrees of improvement in the quality of output images. However, the alteration of the original Floyd and Steinberg algorithm almost always leads to a more complex and time-consuming implementation.

Figure 2.2: Error diffusion kernels: (a) Floyd and Steinberg (1975), (b) Jarvis, Judice and Ninke (1976), (c) Stucki (1981), (d) Fan (1993). “•” represents the pixel being processed.

Another very important issue is bilevel versus multilevel output. The early implementations of the error-diffusion algorithm produced bilevel (black-and-white) reproductions that could be printed by the available devices. Once the technology advanced sufficiently for multilevel output devices to become available, error-diffusion algorithms were adapted to multilevel output^{2,3,30} by introducing of multiple thresholds. For example, the binary case requires a single threshold - usually halfway between the two available levels. The multilevel case requires one less threshold than the number of output levels. As the studies indicate, the transformation from the binary to the multilevel system results in a considerable improvement in image quality of the output^{13,14}.

This research examined the tradeoffs between the number of quantization levels in the color error-diffused images versus the spatial

addressability at which these images were printed. The literature does not indicate that a comprehensive study has been performed to investigate these particular tradeoffs. Sigiura and Makita²⁸ (citing Roetling²⁶) gave a formula that relates the printer's addressability and the number of primary gray levels. However, noting that both of these parameters affect image quality, they resorted to examining image quality by varying only the number of gray levels. Most research in this area concentrated on monochrome or grayscale text^{8,13,14,15} or line art images⁴. Some limited research involving color images¹² has been done for low resolution and/or CRT images as opposed to images printed on devices with high spatial addressability. Appendix A shows an example of an image at various spatial and color resolutions.

The idea of diffusing the error in a perceptually uniform color space such as CIELAB or CIELUV rather than RGB or CMYK device color space was investigated^{18,24,31}. Some authors^{18,24} report improved quality of reproduction when the error is diffused in a device-independent color space (CIELAB, XYZ). Yet, it is noted³³ that the luminance information (L^*) has to be quantized with eight times the resolution of the chrominance information (a^* and b^*). In addition, regardless of the space where the quantization occurs, the final image has to be printed by some device, which means that image ultimately

must be converted to a device-dependent color space (e.g., CMYK). Thus, performing error diffusion in CIELAB will require constant forward and inverse transformations between CMYK (image space) and CIELAB (error space). These color transformations can considerably slow down the image processing.

Therefore, the contributions of this thesis research are intended to help determine the tradeoffs between the degree of quantization and the spatial addressability of color images being quantized via error diffusion in the CMYK color space and printed on a continuous-tone color output device. If it is determined that the increase of either color resolution or spatial addressability (or both) leads to higher perceived quality of images, substantial savings in terms of storage and processing of images could be achieved by choosing the image configuration of the same perceived quality yet actually having lower parameter(s).

3. Approach

3.1 Image Selection

The goal of this research was to investigate the tradeoffs between the number of quantization levels and spatial addressability of printed color images. The realm of color images can be divided into two broad categories: pictorial images and graphics or lineart. Therefore, two of the scenes presented for evaluation were photographic images (“Girl” and “Harbor”), and the third one (“Train”) was a graphic. Appendix B shows all three scenes.

3.2 Image Processing Path

The photographic image original were actual photographs printed on Kodak photographic paper, and the graphic original was a digital file in Encapsulated PostScript (EPS) format. Consequently, the image processing path was somewhat different for the two types of images. Figure 3.1 shows the sequence for the pictorial images. Operations are represented by rectangles, and the color space at each step is indicated by the text next to the arrow. Solid line rectangles designate mandatory steps, whereas dotted ones refer to the optional operations. Resolution adjustment may be optional because an

image at nominal addressability is being processed. The quantization step may be optional because an 8 bit image is being processed.

Figure 3.1: The pictorial image processing path.

The photographic original was scanned and saved as a device RGB file. The scanned image was converted from the device-RGB to device-independent color space using the calibration for the Kodak paper and D50 illuminant. This conversion employed a look-up table (LUT) derived from the calibration. The image in device-independent color space was then converted to CMYK also by using an LUT designed for the particular printer and D50 illuminant. The resolution adjustment steps are described in detail below. The quantization step was performed using error-diffusion algorithm. Finally, the quantized image was printed.

The image processing path for the graphic image is shown in Figure 3.2.

Figure 3.2: The graphic image processing path.

The difference between this path and the pictorial image path is that the CMYK image is obtained not by scanning and then going through the chain of color space conversions, but rather by rasterizing an EPS image.

The error-diffusion algorithm was used with the weights proposed by Fan⁷ shown in Figure 3.3.

Figure 3.3: Error diffusion weights used.

These weights had been shown to reduce the “worming” artifact observed in error-diffused images.

Resolution adjustment consisted of two steps. It was important to maintain the order shown in Figures 3.1 and 3.2, i.e., the two resolution

adjustment steps had to be separated by the quantization step (obviously if this step is needed). Knowing the nominal resolution, it was possible to simulate lower resolutions by using the following two-step process. "Resolution adjustment" reduced both the height and width of the image by some factor using interpolation to minimize the moiré when rescaling periodic images^{30,31}. For instance, if the nominal resolution was 300 dpi and the simulated resolution was 150 dpi, then the resolution factor was 2. Thus, a 1000 × 1000 pixel image became a 500 × 500 pixel image. The second step returned the original image size by converting each pixel to a square of pixels depending on the resolution factor. This conversion was done by using the nearest-neighbor method to duplicate the pixel's digital count. Figure 3.4 shows an example of the two resolution steps done in sequence. The resolution factor is 2, therefore, a 2 × 2 yields a single pixel. If resolution factor is 3, a 3 × 3 square would have yielded a single pixel.

Figure 3.4: An example of resolution adjustment steps.

3.3 Device Calibration

As the imaging paths indicate, up to 2 devices used in creating the output prints: a scanner (for photographic scenes) and a printer. The photographic originals were scanned on the Umax "Power Look" 400 dpi flatbed scanner. The scanner was calibrated for D50 illuminant and Kodak paper. The images were printed on a continuous-tone dye diffusion printer. It was a Tektronix Phaser 440 printer, with the nominal addressability of 300 dpi. The printer was also calibrated for D50 illuminant.

For the given printer, it was necessary to determine its capability to produce enough distinguishable levels to achieve the required color resolution. Two targets were printed to test the printer's color resolution. These targets consisted of a collection of 256 gray patches with each patch representing a single digital count in the range between 0 and 255. This range corresponds to 8 bits per pixel of color resolution. One target had these patches ordered, whereas in the other target, the patches were arranged in random order on the page.

All patches on both targets were measured to obtain their L^* values. The measurements for the patches of equal digital counts were compared to obtain the absolute difference in L^* units. In addition, the L^* values of the patches of

equal digital counts were averaged, and the L^* range that the printer was capable of producing was determined. By using these two values, the number of gray levels that the printer could produce was calculated. Table 3.1 summarizes these results.

Table 3.1: Number of gray levels reproducible on Tektronix Phaser 440.

Average Abs. Difference	Range of L^*	Number of Levels
1.67	83.19	≈ 50

Fifty levels correspond to approximately 5.6 bits of quantization. Therefore, it was safe to claim that more than 5 bpc could be produced on the given continuous-tone printer. This number of gray levels does not necessarily mean that only 50 levels could be produced. These are so called “safe” levels, i.e., at least 50 levels could be produced.

3.4 Test Images

Eighteen images were printed for each of the three original scenes. These 18 images resulted from combining three addressabilities of 100, 150, and 300 dpi with six quantization levels of 2, 4, 8, 16, 32, and 256 levels of gray for each of the four channels (these levels correspond to 1, 2, 3, 4, 5 and 8 bits

per pixel). For 100- and 150-dpi images, resolution adjustment operations were performed. Error-diffusion was required for all levels quantized at fewer than 8 bits per pixel. For example, a 1-bit image contained digital counts 0 and 255, a 2-bit image contained digital counts 0, 85, 170, and 255, and so forth.

Table 3.2 summarizes the physical parameters of the three scenes presented in the experiment.

Table 3.2: Physical parameters of presented images.

	"Girl" Image			"Harbor" Image			"Train" Image		
	100 dpi	150 dpi	300 dpi	100 dpi	150 dpi	300 dpi	100 dpi	150 dpi	300 dpi
Pixels (WxH)	750 × 950	1125 × 1425	2250 × 2850	1000 × 710	1500 × 1065	3000 × 2130	1020 × 590	1530 × 885	3060 × 1770
Size	7.5" × 9.5"			10" × 7.1"			10.2" × 5.9"		

3.5 Experiment Setup and Execution

To achieve the objectives of this research, a graphical rating scale experiment was carried out. Figure 3.5 displays the instructions presented to observers participating in the experiment. A tool written in Java was used to assist in collecting the data. Figure 3.6 shows Graphical User Interface of the data collecting tool. By positioning the diamond on the provided scale, the

observers indicated the perceived quality of the given test image with respect to the two anchors. The width of the scale was 440 units. The mark corresponding to the “Poor” anchor was positioned at 80 units, and the mark corresponding to the “Good” anchor was positioned at 360 units. In between each trial, the diamond was automatically repositioned to the center at 220 units. After all 16 test images for a given scene had been presented, the observer’s answers were saved in a text file. The entries in the file consisted of two numbers for each test image. The first number was the position of the diamond in absolute units, and the second number was the relative score calculated by normalizing the absolute position value by the size of the scale. For instance, an entry in the response file could be:

182 0.413636

Experiment Instructions.

You will be shown 3 series of 16 images. You are to judge the overall quality of each image relative to the perceived quality of the reference images (labeled “Good” and “Poor”). When you have made your judgement, position the pointer on the slider in the location that indicates the relative quality of the test image and press “Next” button to begin the next trial. For example, if the test image appears equal in quality to the “Good” reference image, by clicking at the location marked “Good” position the pointer there. If the test image appears to be lower quality than the “Good” reference, but higher quality than the “Poor” reference, position the pointer between the two marks such that the pointer’s location reflects the relative quality of the test image with respect to the two anchors. You may position the pointer beyond the reference image marks if you feel it is necessary. If you are uncertain about these instructions, please ask the experimenter for clarification.

Thank you for participating in this experiment.

Figure 3.5: Experiment instructions.

☐
Graphical Rating Scale

Scene no.: 1
Next
Image no.: 1

Poor
Good

|

|

|

◆

☐

Figure 3.6: Data collection tool GUI.

The experiment was carried out in a room with lighting simulating D50 illumination. Figure 3.7 depicts the overhead view of the experimental setup.

The images were presented to observers at the normal viewing distance of 35 cm (14 inches). Observer responses were not constrained by any time limits. The graphic image "Train" was always presented as the second scene between the two photographic scenes. The photographic images "Girl" and "Harbor" were presented either as the first or the third scenes. Half of the observers saw the "Girl" image first and the "Harbor" image third, and the other half in reverse order. Within each scene, the test images were presented in random order that was selected from the three possible variations. It took an average 35 minutes for observers to complete the experiment.

Figure 3.7; The overhead view of the experimental setup.

3.6 Observer Selection

All observers participating in the experiment were screened for color deficiencies using Ishihara Pseudoisochromatic Plates and for spatial acuity using a Landolt-C acuity test target (Figure 3.8). At the normal viewing distance of 35 cm, observers with normal spatial acuity should be able to resolve the direction of openings in the rings in the line 6 and not in the line 7.

Figure 3.8: Landolt-C acuity test target.

The screening process resulted in the total of 6 potential observers being rejected (3 each due to color deficiencies and spatial acuity).

A total of 16 observers participated in the experiment. These observers were classified as experienced and inexperienced based on education and experience. Table 3.3 presents the observer statistics.

Table 3.3: The observer statistics.

	No. Persons	No. Males	No. Females	Mean Age (yrs.)	Min. Age (yrs.)	Max. Age (yrs.)
Experienced	8	7	1	33.3	27	48
Inexperienced	8	4	4	31.4	22	41
All	16	11	5	32.3	22	48

4. Results and Discussion

All observer responses were collected, and sorted to order the data 1bpc/100dpi, 1bpc/150dpi, ..., 8bpc/300dpi. Each response was converted to a number between 0 to 100. The data were analyzed done using Microsoft Excel.

The 8bpc/300dpi image is the highest quality image the output system could physically produce. Thus when analyzing the results, the scaled image quality of the test images was compared to that of the 8bpc/300dpi image. By doing so, the optimum image configuration was determined.

4.1 Experienced and Inexperienced Observer Differences

The data were sorted according to the observer groups: experienced vs. inexperienced. It was necessary to determine whether there were significant differences between the two groups. To accomplish this, a paired t -test comparing the mean scale values for each image/scene combination of the two groups with 95% confidence was performed. Appendix C summarizes this analysis. The critical region for a two-tailed t -distribution with 7 degrees of freedom and $\alpha = 0.05$ is $(-\infty, -2.36)$ and $(2.36, +\infty)$. Therefore, if the test statistic falls in this critical region, the two means are concluded to be

significantly different. Of 48 test images (3 scenes with 16 test images) for only 4, the mean scale values were determined to be significantly different. For these 4 images, the t statistic fell in the critical region. The 4 images were “Girl” scene 1bpc/150dpi, “Harbor” scene 1bpc/150dpi, “Train” image 4bpc/150dpi and “Train” scene 4bpc/300dpi.

Considering that the scale values for experienced and inexperienced were significantly different for only slightly over 8% of the images presented, the data for these two groups were pooled to obtain a single set of scale values with higher precision.

4.2 “Girl” Scene

Appendix D presents the scale values for all observers for “Girl” scene. Table 4.1 shows the statistics of these scale values on each image in the scene individually (entries corresponding to the anchors are in italics). Figures 4.1 and 4.2 show the data from Table 4.1 plotted with error bars representing the 95% confidence intervals on the mean estimates.

Using overlapping of confidence intervals as the criterion for two images being perceptually equivalent, the following images were judged to be of the same quality as the 8bpc/300dpi image (bpc - dpi):

8-150, 8-100, 5-300, 5-150, 4-300, 4-150, 3-300.

Table 4.1: "Girl" scene statistics on image-per-image basis.

Image bpc-dpi	Mean	Std. Dev.	95% C.I.	Lower Limit	Upper Limit
1-100	2.50	2.56	1.25	1.25	3.75
1-150	4.13	3.52	1.72	2.40	5.85
1-300	8.13	4.33	2.12	6.00	10.25
2-100	16.25	19.39	9.50	6.75	25.75
2-150	18.00	0.00	0.00	18.00	18.00
2-300	47.69	20.45	10.02	37.67	57.71
3-100	30.31	9.69	4.75	25.56	35.06
3-150	61.94	18.06	8.85	53.09	70.79
3-300	80.19	4.78	2.34	77.85	82.53
4-100	66.13	11.53	5.65	60.48	71.77
4-150	81.25	3.80	1.86	79.39	83.11
4-300	76.63	11.29	5.53	71.09	82.16
5-100	77.94	4.81	2.36	75.58	80.29
5-150	82.00	0.00	0.00	82.00	82.00
5-300	78.69	6.43	3.15	75.54	81.84
8-100	80.44	4.46	2.18	78.25	82.62
8-150	78.38	7.84	3.84	74.53	82.22
8-300	82.81	5.08	2.49	80.33	85.30

Figure 4.1: Scaled image quality for "Girl" scene with number of bits per color as a parameter.

Figure 4.2: Scaled image quality for "Girl" scene with addressability as a parameter.

4.3 “Harbor” Scene

Appendix E presents the scale values for all observers for “Harbor” scene. Table 4.2 shows the statistics of these scale values for each image in the scene individually (entries corresponding to the anchors are in italics). Figures 4.3 and 4.4 show the data from Table 4.2 plotted with error bars representing the 95% confidence intervals on the mean estimates.

The following images were perceived to be of the same quality as the 8bpc/300dpi (bpc - dpi):

8-150, 8-100, 5-300, 5-150, 5-100, 4-300, 4-150, 3-300, 3-150, 2-300.

4.4 “Train” Scene

Appendix F presents the scale values for all observers for “Train” scene. Table 4.3 shows the statistics of these scale values on each image in the scene individually (entries corresponding to the anchors are in italics). Figures 4.5 and 4.6 show the data from Table 4.3 plotted with error bars representing the 95% confidence intervals on the mean estimates.

The following images were perceived to be of the same quality as the 8bpc/300dpi image (bpc - dpi):

5-300, 4-300, 3-300.

Table 4.2: “Harbor” scene statistics on image-per-image basis.

Image bpc-dpi	Mean	Std. Dev.	95% C.I.	Lower Limit	Upper Limit
1-100	2.50	2.25	1.10	1.40	3.60
1-150	5.19	2.95	1.44	3.74	6.63
1-300	7.88	4.50	2.20	5.67	10.08
2-100	11.94	3.59	1.76	10.18	13.69
2-150	18.00	0.00	0.00	18.00	18.00
2-300	73.69	13.04	6.39	67.30	80.08
3-100	39.38	14.41	7.06	32.32	46.43
3-150	72.69	10.56	5.18	67.51	77.86
3-300	84.19	4.17	2.04	82.15	86.23
4-100	62.38	12.94	6.34	56.04	68.71
4-150	76.31	8.78	4.30	72.01	80.62
4-300	83.69	5.88	2.88	80.80	86.57
5-100	73.13	9.82	4.81	68.31	77.94
5-150	82.00	0.00	0.00	82.00	82.00
5-300	79.13	10.90	5.34	73.78	84.47
8-100	70.69	11.13	5.46	65.23	76.14
8-150	80.94	4.46	2.19	78.75	83.12
8-300	79.56	15.97	7.83	71.74	87.39

Figure 4.3: Scaled image quality for "Harbor" scene with number of bits per color as a parameter.

Figure 4.4: Scaled image quality for "Harbor" scene with addressability as a parameter.

Table 4.3: “Train” scene statistics on image-per-image basis.

Image bpc-dpi	Mean	Std. Dev.	95% C.I.	Lower Limit	Upper Limit
1-100	4.31	2.77	1.36	2.95	5.67
1-150	7.25	5.04	2.47	4.78	9.72
1-300	8.94	4.01	1.96	6.97	10.90
2-100	12.25	3.73	1.83	10.42	14.08
2-150	18.00	0.00	0.00	18.00	18.00
2-300	43.81	16.11	7.90	35.92	51.71
3-100	22.31	6.69	3.28	19.03	25.59
3-150	57.06	13.88	6.80	50.26	63.86
3-300	84.13	8.00	3.92	80.21	88.04
4-100	48.44	15.38	7.53	40.90	55.97
4-150	77.50	6.69	3.28	74.22	80.78
4-300	86.06	5.69	2.79	83.28	88.85
5-100	56.38	15.66	7.67	48.70	64.05
5-150	82.00	0.00	0.00	82.00	82.00
5-300	87.56	5.21	2.56	85.01	90.12
8-100	60.13	15.67	7.68	52.45	67.80
8-150	80.31	2.94	1.44	78.87	81.75
8-300	84.75	4.80	2.35	82.40	87.10

Figure 4.5: Scaled image quality for "Train" scene with number of bits per color as a parameter.

Figure 4.6: Scaled image quality for "Train" scene with addressability as a parameter.

4.5 *Photographic Scenes*

The scaled image quality ratings for photographic scenes exhibited a lot of similarities. Therefore, it was useful to determine whether the data for these two scenes could be pooled to obtain image quality ratings with higher precision. Similarly to the analysis of experienced vs. inexperienced observer data, a paired *t*-test was performed to compare the mean scale values for each image for the two scenes with 95% confidence. Appendix G summarizes this analysis. The critical region for a two-tailed *t*-distribution with 15 degrees of freedom and α of 0.05 is $(-\infty, -2.13)$ and $(2.13, +\infty)$. Therefore, if the test statistic falls in this critical region, the two means are concluded to be significantly different.

Out of 16 images, only 5 were determined to have mean scale values significantly different for the two scenes. Therefore, the data for the two photographic scenes were pooled together, and the resulting statistics are shown in Table 4.4. Figures 4.7 and 4.8 depict those results plotted with error bars representing the 95% confidence intervals on the mean estimates.

The following images were perceived to be of the same quality as the 8bpc/300dpi (bpc - dpi):

Table 4.4: Photographic scenes statistics on image-per-image basis.

Image bpc-dpi	Mean	Std. Dev.	95% C.I.	Lower Limit	Upper Limit
1-100	2.50	2.37	0.82	1.68	3.32
1-150	4.66	3.24	1.12	3.53	5.78
1-300	8.00	4.35	1.51	6.49	9.51
2-100	14.09	13.89	4.81	9.28	18.91
2-150	18.00	0.00	0.00	18.00	18.00
2-300	60.69	21.42	7.42	53.26	68.11
3-100	34.84	12.93	4.48	30.36	39.32
3-150	67.31	15.54	5.39	61.93	72.70
3-300	82.19	4.86	1.68	80.51	83.87
4-100	64.25	12.20	4.23	60.02	68.48
4-150	78.78	7.12	2.47	76.32	81.25
4-300	80.16	9.55	3.31	76.85	83.47
5-100	75.53	7.99	2.77	72.76	78.30
5-150	82.00	0.00	0.00	82.00	82.00
5-300	78.91	8.80	3.05	75.86	81.96
8-100	75.56	9.70	3.36	72.20	78.92
8-150	79.66	6.41	2.22	77.44	81.88
8-300	81.19	11.77	4.08	77.11	85.27

Figure 4.7: Scaled image quality for photographic scenes with number of bits per color as a parameter.

Figure 4.8: Scaled image quality for photographic scenes with addressability as a parameter.

8-150, 8-100, 5-300, 5-150, 5-100, 4-300, 4-150, 3-300.

4.6 Discussion

Table 4.5 lists the images that were rated equivalent in quality to 8bpc/300dpi image.

Table 4.5: Images equivalent to 8bpc/300dpi.

scene	list of images equivalent to 8bpc/300dpi (bpc-dpi)
"Girl"	8-150, 8-100, 5-300, 5-150, 4-300, 4-150, 3-300
"Harbor"	8-150, 8-100, 5-300, 5-150, 5-100, 4-300, 4-150, 3-300, 3-150, 2-300
"Train"	5-300, 4-300, 3-300
Photographic	8-150, 8-100, 5-300, 5-150, 5-100, 4-300, 4-150, 3-300

From these results the following can be noted:

- *"Girl" scene*: maintaining the same image quality as the 8bpc/300dpi image, the minimum number of bits per pixel needed is 3 at 300 dpi, and the lowest addressability is 100 dpi at 8 bpc.
- *"Harbor" scene*: maintaining the same image quality as the 8bpc/300dpi image, the minimum number of bits per pixel needed is 2 at 300 dpi, and the lowest addressability is 100 dpi at 5 bpc.
- *"Train" scene*: maintaining the same image quality as the 8bpc/300dpi

image, the minimum number of bits per pixel needed is 3 at 300 dpi, and no other addressability is acceptable.

- *Photographic scenes*: maintaining the same image quality as the 8bpc/300dpi image, the minimum number of bits per pixel needed is 3 at 300 dpi, and the lowest addressability is 100 dpi at 5 bpc.

There is a clear difference between the results for the two types of scenes. Decreasing the addressability is acceptable for photographic scenes, however, this is not true for the graphics scene. In a graphics scene that has relatively few colors, sharp fine lines, and large uniform areas, even a small reduction in resolution exhibits the objectionable “jaggies” and moiré patterns. There also exist the differences in the results between the two photographic scenes. The observers rated fewer images to be as good as the 8bpc/300dpi image for the “Girl” scene than for the “Harbor” scene. This can be explained by greater observer sensitivities to the contouring on a human face showing at lower color resolution and addressability than to the same artifacts occurring in the image areas containing water and sky.

Figures 4.9 through 4.12 are 3-D bar graphs where bars with black tops show 8bpc/300dpi image and the ones equal to it in perceived quality.

Figure 4.9: "Girl" scene scaled image quality 3-D bar graph.

Figure 4.10: "Harbor" scene scaled image quality 3-D bar graph.

Figure 4.11: "Train" scene scaled image quality 3-D bar graph.

Figure 4.12: Photographic scenes scaled image quality 3-D bar graph.

The obtained results should be interpreted using the measure of information capacity IC :

$$IC = N \times M \times \log_2(\#levels) \times (\#channels),$$

where N and M correspond to the width and height of the image, $\log_2(\#levels)$ is the number of bits per channel, and number of channels for a CMYK image is 4. By examining the tradeoffs from this perspective, the optimum allocation of computer bits between color and spatial resolution can be determined. Table 4.6 lists the IC values for each image presented in the experiment normalized to the IC of 8bpc/300dpi.

As seen from the data in Table 4.6, it is more beneficial to allocate the bits in the computer file to color resolution rather than to storing more pixels at lower bits per pixel. For instance, a 5bpc/150dpi file is smaller than a 3bpc/300dpi file by a factor of $\frac{0.3750}{0.1563} = 2.4$. If the two images are of the same physical size in terms of length units (say 1" $\times$ 1"), a 150 dpi image is 150 $\times$ 150 pixels and 300 dpi image is 300 $\times$ 300 pixels, then the storage sizes are 112,500 bits per color channel and 270,000 bits per color channel respectively. For a CMYK color image, the total image sizes are 450,000 bits and 1,080,000 bits respectively.

Table 4.6: Information capacity for images in the experiment.

Images	IC
1-100	0.0139
1-150	0.0313
1-300	0.1250
2-100	0.0278
2-150	0.0625
2-300	0.2500
3-100	0.0417
3-150	0.0938
3-300	0.3750
4-100	0.0556
4-150	0.1250
4-300	0.5000
5-100	0.0694
5-150	0.1563
5-300	0.6250
8-100	0.1111
8-150	0.2500
8-300	1.0000

Tables 4.7 through 4.10 list the images equivalent to 8bpc/300dpi together with their respective ICs for each of the scenes.

Table 4.7: "Girl" scene images equivalent to 8bpc/300dpi with ICs.

Image (bpc-dpi)	3-300	4-150	4-300	5-150	5-300	8-100	8-150
IC	0.3750	0.1250	0.5000	0.1563	0.6250	0.1111	0.2500

Table 4.8: "Harbor" scene images equivalent to 8bpc/300dpi with ICs.

Image (bpc-dpi)	2-300	3-150	3-300	4-150	4-300	5-100	5-150	5-300	8-100	8-150
IC	0.2500	0.0938	0.3750	0.1250	0.5000	0.0694	0.1563	0.6250	0.1111	0.2500

Table 4.9: "Train" scene images equivalent to 8bpc/300dpi with ICs.

Image (bpc-dpi)	3-300	4-300	5-300
IC	0.3750	0.5000	0.6250

Table 4.10: Photographic scenes images equivalent to 8bpc/300dpi with ICs.

Image (bpc-dpi)	3-300	4-150	4-300	5-100	5-150	5-300	8-100	8-150
IC	0.3750	0.1250	0.5000	0.0694	0.1563	0.6250	0.1111	0.2500

Now looking at the tradeoffs between color and spatial resolutions, the consideration can be given not only to the lowest values for each parameter but also to the combination that results in the smallest IC value. For the "Girl" scene, the image that is equivalent in quality to the best available (8bpc/300dpi), and that has the lowest IC is the 8bpc/100dpi image. For the photographic scenes, it is the 5bpc/100dpi image, while for the "Train" scene, it

is the 3bpc/300dpi image. Where the type of the scene allows (photographic), retaining relatively high color resolution allows for printing images at low addressability without sacrificing perceived image quality at normal viewing distances.

The tradeoffs between color resolution and addressability are scene dependent. Photographic scenes can sustain greater reduction in addressability without loss of perceived image quality than graphics. As this experiment showed, the photographic scenes may be printed with 5 bpc at 100 dpi, while graphics images require 3 bpc at 300 dpi. If a single bpc/dpi combination is to be considered optimum compared to 8bpc/300dpi, it would have to be 3bpc/300dpi because this combination was found to be equivalent in quality to the best possible image at the normal viewing distance.

5. Conclusions

A psychophysical experiment was designed and carried out to investigate the tradeoffs between the degree of quantization and addressability of color images. The results of the experiment were interpreted with respect to the best physically possible image for the given system: 8 bits per pixel, at 300 dpi. These results show that an optimum image configuration regardless of the scene is 3 bits per pixel, at 300 dpi. However, for photographic scenes there can be even greater gains because the addressability required to maintain the same perceived image quality is lower than 300 dpi.

Commonly, an image printed at higher addressability is regarded to be of higher quality. Though this may be true for text, it is not necessarily so for photographic and graphic scenes. For such scenes, color resolution plays an increasingly important role. If the issue is maintaining the image quality and keeping the storage constant, it is more beneficial to allocate computer resources to store an image with higher degree of quantization and lower addressability.

6. References

1. C. J. Bartleson and F. Grum, *Optical Radiation Measurements Volume 5: Visual Measurements*, Academic Press, Orlando, FL, 1984.
2. D. Birnbaum, R. Eschbach and K. Knox, Under-compensated Error Diffusion for Multi-level Printing, *Color Hard Copy and Graphic Arts II, SPIE*, vol. 1912, 1993, pp. 482-487.
3. M. Broja, K. Michalowski and O. Bryngdahl, Error Diffusion Concept for Multi-level Quantization, *Optics Communications*, vol. 79, no. 5, November 1990, pp. 280-284.
4. N. Burningham and Y. Ng, Image Quality Study of Printers with Various Resolution and Gray Levels, *Proceedings of IS&T's Eighth International Congress on Advances in Non-Impact Printing Technology*, 1992, pp. 500-505.
5. P. A. Delabastita, Multilevel Halftoning, *IS&T's Fourth Technical Symposium in Prepress, Proofing & Printing*, 1985, pp. 68-73.
6. M. Ester, Image Quality and Viewer Perception, *Leonardo*, Digital Image - Digital Cinema Supplemental Issue, 1990, pp. 51-63.
7. Z. Fan, A Simple Modification of Error Diffusion Weights, *IS&T's 46th Annual Conference*, IS&T Final Program and Advance Printing of Paper Summaries, 1993, pp. 113-114.

8. J. E. Farrel, Grayscale and Resolution Tradeoffs in Photographic Image Quality, Digital Imaging Conference, 1997.
9. G. S. Fawcett and G. F. Schrack, Halftoning Techniques Using Error Correction, *Proceedings of the SID*, vol 27, no. 4, 1986, pp. 305-308.
10. R. Floyd and L. Steinberg, An Adaptive Algorithm for Spatial Grey Scale, *Society for Information Display 1975 Symposium Digest of Technical Papers*, 1975, pp. 36-37.
11. J. D. Foley, A. van Dam, S. K. Feiner and J. F. Hughes, *Computer Graphics: Principles and Practice*, 2nd ed., Addison - Wesley, Reading, MA, 1990.
12. R. S. Gentile, E. Walowit and J. P. Allebach, Quantization and Multilevel Halftoning of Color Images for Near-Original Image Quality, *Journal of Optical Society of America*, vol. 7, no. 6, June 1990, pp. 1019-1026.
13. J. Gille, R. Martin and J. Larimer, Spatial Resolution, Grayscale, and Error Diffusion Trade-offs: Impact on Display System Design, *Conference Record on the 1994 International Display Research Conference*, pp. 381-385.
14. J. Gille, R. Martin, J. Lubin and J. Larimer, Grayscale/Resolution Tradeoff for Text: Model Predictions and Psychophysical Results for Letter Confusion and Letter Discrimination, *Proceedings of Human Vision, Visual Processing and Display VI, SPIE*, vol. 2411, 1995, pp. 159-169.

15. J. Gille, R. Samadani, R. Martin and J. Larimer, Grayscale/Resolution Tradeoff, *SPIE*, vol. 2179, pp. 47-59.
16. R. C. Gonzalez and R. E. Woods, *Digital Image Processing*, Addison - Wesley, Reading, MA, 1992.
17. T. A. Grogan and M. Wu, Image Quality Measurements with a Neural Brightness Perception Model, *Proceedings of Human Vision, Visual Processing, and Digital Display II*, *SPIE*, vol. 1453, 1991, pp. 16-25.
18. H. Haneishi, N. Shimoyama and Y. Miyake, Color Digital Halftoning for Colorimetric Color Reproduction, *Recent Progress in Digital Halftoning*, edited by R. Eschbach, IS&T, 1994.
19. K. T. Knox, Error Diffusion: A Theoretical View, *SPIE*, vol. 1913, pp. 326-331.
20. K. T. Knox and R. Eschbach, Threshold Modulation in Error Diffusion, *Journal of Electronic Imaging*, vol. 2, no. 3, 1993, pp. 185-192.
21. B. W. Kolpatzik and C. A. Bouman, Optimized Error Diffusion Based on a Human Visual Model, *Human Vision, Visual Processing, and Digital Display III*, *SPIE*, vol. 1666, 1992, pp. 152-164.
22. Q. Lin, Halftone Image Quality Analysis Based on a Human Vision Model, *SPIE*, vol. 1913, pp. 378 - 389.

23. M. Mahy, L. Van Eycken, P. Wambacq and A. Oosterlinck, Evaluation of Uniform Colour Spaces for Image Processing, *TAGA Proceedings*, 1994, pp. 179-198.
24. G. Marcu and S. Abe, An Error Diffusion Method for Color Reproduction in Ink Jet Printing, *Recent Progress in Digital Halftoning*, edited by R. Eschbach, IS&T, 1994.
25. T. N. Pappas and D. L. Neuhoff, Printer Models and Error Diffusion, *IEEE Transactions on Image Processing*, vol. 4, no. 1, January 1995, pp. 66-80.
26. P. Roetling, Visual Performance and Image Coding, *SPIE/OSA on Image Processing*, vol. 74, 1976, pp. 195-199.
27. D. A. Schumacher, A Comparison of Digital Halftoning Techniques, *Graphics Gems II*, edited by J. Arvo, Academic Press, Boston, MA, 1991.
28. S. Sugiura and T. Makita, An Improved Multilevel Error Diffusion Method, *Journal of Imaging Science and Technology*, vol. 39, no. 6, November/December 1995, pp. 495-501.
29. J. Sullivan, R. Miller and G. Pios, Image Halftoning Using a Visual Model in Error Diffusion, *Journal of Optical Society of America*, vol. 10, no. 8, August 1993, pp. 1714-1724.
30. R. Ulichney, *Digital Halftoning*, MIT Press, Cambridge, MA, 1987.

31. U.S. Patent #05208871, Pixel Quantization with Adaptive Error Diffusion, R. Eschbach, Xerox Corp., 1993.
32. U.S. Patent #05226094, Method for Making Image Conversion with Error Diffusion, R. Eschbach, Xerox Corp., 1993.
33. D. Venable, J. Stinehour and P. Roetling, Selection and Use of Small Color Sets for Pictorial Display, *SPSE's 43rd Annual Conference*, Advanced Printing of Conference Summaries, 1990, pp. 90-92.

Appendix A: *An Example of an Image at Different Spatial and Color Resolutions.*

8 bit image at 300 dpi

8 bit image at 150 dpi

8 bit image at 100 dpi

4 bit image at 300 dpi

2 bit image at 300 dpi

Appendix B: *Experiment Scenes.*

Appendix C: Paired t-Test Results of Mean Scale Values with 95% Confidence for Experienced and Inexperienced Observers.

Images		Experienced		Inexperienced		<i>t</i> statistic	In Crit. Reg.
Scene	bpc-dpi	Mean	Vari- ance	Mean	Vari- ance		
"Girl"	1-100	1.50	2.86	3.50	8.86	-1.53	N
	1-150	2.25	4.79	6.00	13.71	-3.52	Y
	1-300	7.25	18.50	9.00	20.00	-0.70	N
	2-100	11.38	15.13	21.13	736.13	-1.02	N
	2-300	41.88	384.13	53.50	434.57	-0.87	N
	3-100	31.00	87.14	29.63	113.13	0.23	N
	3-150	61.38	311.98	62.50	386.00	-0.10	N
	3-300	80.63	13.13	79.75	35.36	0.54	N
	4-100	65.00	169.14	67.25	112.79	-0.41	N
	4-150	80.86	6.41	81.63	24.27	-0.69	N
	4-300	80.00	27.41	73.25	219.36	1.20	N
	5-100	78.63	11.98	77.25	36.50	0.45	N
	5-300	78.63	73.13	78.75	15.36	-0.04	N
	8-100	82.50	12.86	78.38	19.98	2.04	N
	8-150	76.25	112.79	80.50	8.57	-1.42	N
	8-300	81.00	11.43	84.63	36.27	-1.66	N

"Ha-rbor"	1-100	2.50	6.57	2.50	4.29	0	N
	1-150	3.50	6.00	6.00	6.13	-3.58	Y
	1-300	6.75	17.07	9.00	23.43	-1.19	N
	2-100	12.88	17.84	11.00	7.71	1.23	N
	2-300	70.38	153.13	77.00	186.00	-1.03	N
	3-100	38.63	74.55	40.13	368.98	-0.20	N
	3-150	75.75	68.21	69.63	149.41	1.41	N
	3-300	84.75	20.50	83.63	15.98	0.46	N
	4-100	63.50	163.43	61.25	192.21	0.28	N
	4-150	76.63	81.98	76.00	83.14	0.14	N
	4-300	81.00	13.71	86.38	43.98	-1.64	N
	5-100	75.75	71.07	70.50	120.00	1.23	N
	5-300	79.75	172.50	78.50	81.14	0.21	N
	8-100	75.50	38.00	65.88	174.70	1.49	N
	8-150	82.00	1.14	79.88	38.98	0.97	N
	8-300	77	484.86	82.13	46.70	-0.62	N

"Train"	1-100	4.63	11.41	4.00	4.86	0.55	N
	1-150	5.13	15.55	9.38	28.55	-2.05	N
	1-300	8.00	28.57	9.88	3.84	-1.21	N
	2-100	12.75	9.64	11.75	19.64	0.50	N
	2-300	41.25	190.50	46.38	350.84	-0.41	N
	3-100	22.00	72.00	22.63	23.70	-0.18	N
	3-150	51.63	132.27	62.50	213.14	-1.49	N
	3-300	82.75	31.93	85.50	100.86	-0.55	N
	4-100	43.75	251.07	53.13	205.27	-1.66	N
	4-150	73.50	54.00	81.50	5.43	-3.77	Y
	4-300	82.50	18.29	89.63	21.98	-2.72	Y
	5-100	58.38	424.55	54.38	91.98	0.39	N
	5-300	86.75	27.64	88.38	29.13	-0.54	N
	8-100	62.25	387.36	58.00	128.29	0.45	N
	8-150	80.25	16.79	80.38	1.70	-0.08	N
	8-300	83.38	5.70	86.13	39.28	-1.09	N

Appendix D: "Girl" Scene Scale Values.

Image	Observers															
	experienced								inexperienced							
	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	#11	#12	#13	#14	#15	#16
1-100	0	2	0	0	2	5	2	1	2	8	7	1	5	1	0	4
1-150	0	7	3	1	1	3	1	2	2	11	10	6	8	1	3	7
1-300	4	10	12	2	7	13	2	8	10	14	12	9	4	1	13	9
2-100	3	15	13	12	9	14	11	14	8	15	12	88	14	9	10	13
2-150	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
2-300	55	77	52	50	26	27	23	25	31	32	50	44	43	91	67	70
3-100	41	40	39	31	15	25	23	34	31	33	28	14	50	23	35	23
3-150	75	50	65	82	85	40	48	46	38	80	37	50	81	82	55	77
3-300	76	85	76	82	82	85	78	81	73	82	79	73	82	90	75	84
4-100	59	55	50	82	72	73	79	50	58	80	50	61	78	64	74	73
4-150	82	80	75	82	83	81	82	82	88	80	71	83	82	85	82	82
4-300	83	84	75	81	69	83	82	83	46	80	69	59	80	91	75	86
5-100	82	75	78	80	73	82	77	82	74	77	82	73	82	67	86	77
5-150	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82
5-300	82	81	82	82	58	78	85	81	83	76	73	76	76	82	81	83
8-100	82	82	89	81	85	77	80	84	80	80	75	76	82	72	86	76
8-150	82	82	70	82	79	82	52	81	79	83	82	82	82	82	74	80
8-300	82	81	82	82	75	85	84	77	80	81	79	85	84	98	83	87

Appendix E: "Harbor" Scene Scale Values.

Image	Observers															
	experienced								inexperienced							
	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	#11	#12	#13	#14	#15	#16
1-100	0	4	7	1	2	1	5	0	1	2	3	0	6	2	1	5
1-150	4	3	5	0	8	1	3	4	5	9	10	2	7	8	7	7
1-300	1	8	10	1	10	11	9	4	3	6	17	13	12	10	4	7
2-100	8	8	17	20	10	13	14	13	12	7	15	10	12	8	14	10
2-150	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
2-300	68	55	83	50	85	74	75	73	76	83	50	64	82	83	92	86
3-100	50	34	30	50	40	41	26	38	38	31	20	31	82	37	52	30
3-150	82	79	61	81	81	73	66	83	60	83	48	63	82	71	80	70
3-300	82	93	82	83	82	82	83	91	86	86	82	82	86	82	89	76
4-100	66	50	59	80	78	56	46	73	62	79	48	42	70	50	78	61
4-150	71	75	83	82	57	81	84	80	59	80	80	68	82	82	86	71
4-300	82	79	87	74	80	83	81	82	80	82	83	100	81	91	87	87
5-100	76	82	65	82	80	61	84	76	77	80	64	50	82	63	70	78
5-150	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82
5-300	82	89	87	82	48	81	83	86	88	82	81	60	82	83	82	70
8-100	77	73	68	80	65	81	80	80	46	79	77	67	82	50	62	64
8-150	84	81	81	82	83	82	81	82	82	81	79	65	83	82	82	85
8-300	82	90	84	82	23	85	82	88	87	81	67	87	82	81	89	83

Appendix F: "Train" Scene Scale Values.

Image	Observers															
	experienced								inexperienced							
	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	#11	#12	#13	#14	#15	#16
1-100	5	1	8	3	4	6	10	0	4	3	7	2	7	1	5	3
1-150	3	5	13	1	8	5	5	1	11	12	11	1	11	1	15	13
1-300	13	1	16	3	6	9	12	4	13	9	12	7	9	9	9	11
2-100	14	7	17	10	12	13	15	14	9	15	15	13	13	2	12	15
2-150	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
2-300	54	50	39	22	32	64	38	31	35	31	48	38	87	34	59	39
3-100	42	17	23	18	22	15	19	20	25	21	24	21	13	30	22	25
3-150	65	58	50	60	33	62	45	40	60	76	67	55	82	50	72	38
3-300	73	82	87	82	81	82	82	93	86	84	88	91	87	98	87	63
4-100	57	47	24	70	32	54	36	30	61	60	35	68	50	35	72	44
4-150	80	67	72	71	80	79	60	79	86	80	82	82	82	82	78	80
4-300	82	90	84	75	82	82	80	85	92	85	90	90	90	99	87	84
5-100	56	69	25	79	84	69	47	38	59	49	66	50	50	37	61	63
5-150	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82
5-300	85	98	88	82	84	84	83	90	92	84	87	88	87	99	81	89
8-100	77	64	47	88	76	58	63	25	42	54	57	66	50	50	70	75
8-150	82	82	71	82	81	78	84	82	79	79	80	79	82	81	82	81
8-300	85	88	81	82	82	82	85	82	87	83	87	83	88	99	85	77

Appendix G: Paired t-Test Results of Mean Scale Values with 95% Confidence for “Girl” and “Harbor” Scenes.

Images bpc-dpi	“Girl” Scene		“Harbor” Scene		<i>t</i> statistic	In Crit. Region
	Mean	Variance	Mean	Variance		
1-100	2.5	6.53	2.5	5.07	0	N
1-150	4.13	12.38	5.19	8.70	-1.24	N
1-300	8.13	18.78	7.88	20.25	0.18	N
2-100	16.25	375.93	11.94	12.86	0.86	N
2-300	47.69	418.10	73.69	169.96	-4.25	Y
3-100	30.32	93.96	39.38	207.58	-3.05	Y
3-150	61.94	326.06	72.69	111.56	-2.84	Y
3-300	80.19	22.83	84.19	17.36	-2.47	Y
4-100	66.13	132.92	62.38	167.32	1.12	N
4-150	81.25	14.47	76.31	77.16	1.80	N
4-300	76.63	127.45	83.69	34.63	-2.10	N
5-100	77.94	23.13	73.13	96.52	1.86	N
5-300	78.69	41.30	79.13	118.78	-0.24	N
8-100	80.44	19.86	70.69	123.96	3.46	Y
8-150	78.38	61.45	80.94	19.93	-1.11	N
8-300	82.81	25.76	79.56	255.06	0.88	N